

Printing date 16.09.2017

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 16.09.2017

	Tilling date 10.09.2017	version number 5	Kevision. 10.09.201
	SECTION 1: Identificati	on of the substance/mixture and of	the company/undertaking
	- 1.1 Product identifier		
	- Trade name: Xeramic® Threa	the substance or mixture and uses advised available.	d against
	 - 1.3 Details of the supplier of th - Manufacturer/Supplier: Petromark Automotive Chemicals Rooswijkweg 316 NL-1951 ME Velsen-Noord 		
	The Netherlands www.petromark.eu		
	 Further information obtainab Department issuing MSDS: in 1.4 Emergency telephone num 	fo@petromark.eu	
	SECTION 2: Hazards id	entification	
	- 2.1 Classification of the substa	ance or mixture	
	- Classification according to Re	-	
	Aquatic Chronic 3 H412 Harm	ful to aquatic life with long lasting effects.	
	 Hazard pictograms Void Signal word Void Hazard statements H412 Harmful to aquatic life with the environment of the e	onment. iner in accordance with local/regional/nation he contents do not exceed 125 ml ith long lasting effects.	al/international regulations.
_	-	on/information on ingredients	
	- 3.2 Mixtures - Description: Adhesive		
	- Dangerous components:		
ſ	CAS: 128-37-0 Antioxida	nt BHT	≥ 0.25 - < 1%
L	EINECS: 204-881-4 Aquatic A	cute 1, H400; Aquatic Chronic 1, H410	
L			(Contd. on page 2

Printing date 16.09.2017

Version number 3

Revision: 16.09.2017

Trade name: Xeramic® Threadlocker Blue 20180

		(Contd. of page 1)
CAS: 80-15-9	a,a -dimethylbenzyl hydroperoxide	≥ 0.25 - < 1%
EINECS: 201-254-7	Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373; Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335	
CAS: 114-83-0	2'-phenylacetohydrazide	≥ 0.1 - < 1%
EINECS: 204-055-3	Acute Tox. 3, H301	
- Additional information: For the wording of the listed hazard phrases refer to section 16.		

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information: Remove any clothing soiled by the product.

- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: After contact with skin, wash with plenty of water.

- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

- 4.2 Most important symptoms and effects, both acute and delayed

- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Avoid contact with the eyes and skin.
- 6.2 Environmental precautions:
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow product to reach sewage system or any water course.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

GBGEN

Ve

Revision: 16.09.2017

Trade name: Xeramic® Threadlocker Blue 20180

Dispose of the material collected according to regulations.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

-7.1 Precautions for safe handling No special precautions are necessary if used correctly.

- Information about fire - and explosion protection:

No special precautions are necessary if used and stored according to specifications.

-7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13

-7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.

- -8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.

- -8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work. - **Respiratory protection:** Not required.

- Respiratory protection: - Protection of hands:
- Protection of hands:

Protective gloves on prolonged contact with skin.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation - Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

Permeation time / penetration time: = 480 minutes (DIN EN 374): Naturlatex I, Nr. 0395 oder 0403 Chloropren Nitril I, Nr. 0727 Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836 Viton, Nr. 0890 Butyl II, Nr. 0897 Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):



Printing date 16.09.2017

(Contd. of page 2)

Version number 3

Printing date 16.09.2017

Version number 3

Revision: 16.09.2017

Trade name: Xeramic® Threadlocker Blue 20180

(Contd. of page 3)

Chloropren Nitril II, Nr. 0717 Nitril VI, Nr. 0754 Nitril V, Nr. 0764

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplierÕ recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: Avoid contact with the eyes.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and c	hemical properties
- General Information	
- Appearance: Form:	TL.: 4
Form: Colour:	Fluid Blue
- Odour:	Mild
- Odour: - Odour threshold:	Not determined.
- pH-value:	Not determined.
•	
- Change in condition	T. J
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Undetermined.
- Flash point:	> 100 ; C
- Flammability (solid, gas):	Not applicable.
- Ignition temperature:	
Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
- Vapour pressure:	Not determined.
- Density at 25 °C:	1,12 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
	(Contd. on page

Revision: 16.09.2017

Trade name: Xeramic® Threadlocker Blue 20180

	(Contd. of page 4)
1 500 - 3 000 mPas (Brookfield 3/20)	
Not determined.	
No further relevant information available.	
	Not determined.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

- No decomposition if used and stored according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with metal-salts.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

80-15-9 α,α -dimethylbenzyl hydroperoxide				
Oral		382 mg/kg (rat)		
Dermal	LD50	500 mg/kg (rat)		
Inhalative	LC50/4 h	220 mg/l (rat)		
114-83-0 2'-phenylacetohydrazide				
Oral	LD50	270 mg/kg (rat)		

- Primary irritant effect:
- Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.
- Serious eye damage/irritation Slight irritant effect possible.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- No experimentally found toxicological data are available for this preparation.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- Remark: Harmful to fish

(Contd. on page 6)



Printing date 16.09.2017

Version number 3

Revision: 16.09.2017

Trade name: Xeramic® Threadlocker Blue 20180

(Contd. of page 5)

- Additional ecological information:

- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

-13.1 Waste treatment methods

- Recommendation Disposal must be made according to official regulations.

- European waste catalogue		
	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)	
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09	

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information -14.1 UN-Number Void - ADR, IMDG, IATA - 14.2 UN proper shipping name - ADR, IMDG, IATA Void - 14.3 Transport hazard class(es) - ADR, ADN, IMDG, IATA - Class Void -14.4 Packing group - ADR, IMDG, IATA Void - 14.5 Environmental hazards: Not applicable. -14.6 Special precautions for user Not applicable. - 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. - UN "Model Regulation": Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

- National regulations:

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

Printing date 16.09.2017

Version number 3

PETROMARK[®]

Printing date 16.09.2017

Safety data sheet according to 1907/2006/EC, Article 31

Version number 3

Revision: 16.09.2017

Trade name: Xeramic® Threadlocker Blue 20180

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 6)

SECTION 16: Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. - Relevant phrases H242 Heating may cause a fire. H301 Toxic if swallowed. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H331 Toxic if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. - Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. E: Organic peroxides DType E/F Acute Tox. 4: Acute toxicity DCategory 4 Acute Tox. 3: Acute toxicity DCategory 3 Skin Corr. 1B: Skin corrosion/irritation DCategory 1B STOT SE 3: Specific target organ toxicity (single exposure) DCategory 3 STOT RE 2: Specific target organ toxicity (repeated exposure) DCategory 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard DCategory 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard DCategory 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard DCategory 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard DCategory 3 -* Data compared to the previous version altered. GBGEN