

Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

· Article number: 20313

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC35 Washing and cleaning products (including solvent based products)

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

· Application of the substance / the mixture Cleaner solvent

## • 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier:

Petromark Automotive Chemicals Rooswijkweg 316, 1951 ME Velsen-Noord, The Netherlands www.petromark.eu info@petromark.eu

· Further information obtainable from:

Petromark Automotive Chemicals: info@petromark.eu

· 1.4 Emergency telephone number:

Petromark Automotive Chemicals

Tel. +31 (0)251 211397

Tel. +31 (0)251 211397

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02

- · Signal word Danger
- · Hazard-determining components of labelling:

Alkanes (C11-C12), iso-alkanes, <2% aromates

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 1)

H413 May cause long lasting harmful effects to aquatic life.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection.

P273 Avoid release to the environment.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a doctor.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P331 Do NOT induce vomiting.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Active substance with propellant

· Dangerous components:			
EC number: 918-167-1	Alkanes (C11-C12), iso-alkanes, <2% aromates	50-<75%	
	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 4, H413		
CAS: 106-97-8	butane (containing < 0.1% butadiene (203-450-8))	10-<25%	
EINECS: 203-448-7	Flam. Gas 1, H220; Press. Gas C, H280		
CAS: 74-98-6	propane	10-<25%	
EINECS: 200-827-9	Flam. Gas 1, H220; Press. Gas C, H280		
CAS: 37205-87-1	CAS: 37205-87-1 Isononylphenol, ethoxylated (3-7 EO)		
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319		

· Ingredients according to detergents guidline 648/2004/EC	
aliphatic hydrocarbons	≥ 30%
non-ionic surfactants	< 5%

· Additional information:

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 2)

 $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- $\cdot$  Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

(Contd. on page 4)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

### 106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### 74-98-6 propane

OEL Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Filter A/P2

#### · Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5 \text{ mm}$ 

#### · Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 4)

• Eye protection: Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

**Boiling point/Boiling range:** -44 °C

· Flash point: -97 °C

· **Self-igniting:** Product is not selfigniting.

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

**Lower:** 0.6 Vol % Upper: 10.9 Vol %

· Vapour pressure at 20 °C: 8300 hPa

• Density at 20 °C: 0.66 g/cm<sup>3</sup>
• Relative density Not determined.

Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 98.2 %

• **9.2 Other information** No further relevant information available.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 5)

- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
Alkanes (C11-C12), iso-alkanes, <2% aromates			
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50(8h)	>5000 mg/m3 (rat)	
37205-87-	37205-87-1 Isononylphenol, ethoxylated (3-7 EO)		
Oral	LD50	>2000 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:		
Alkanes (C11-C12), iso-alkanes, <2% aromates		
EL0 (48h)	1000 mg/l (Daphnia magna)	
EL0(72h)	1000 mg/l (Pseudokirchneriella subcapitata)	
NOELR (72h)	1000 mg/l (Pseudokirchneriella subcapitata)	
LL0(96h)	1000 mg/l (Oncorhynchus mykiss (96h))	
NOEC (21 days)	0.011 mg/l (Daphnia magna)	
37205-87-1 Isononylphenol, ethoxylated (3-7 EO)		
LC50	1-10 mg/l (Fish)	
EC50	1-10 mg/l (algae 72h)	
	1-10 mg/l (Daphnia Magna 48h)	

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 6)

• 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

1,1,2,2,2,2	
14.1 UN-Number ADR, ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR, ADN	UN1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Label	2.1
ADN	
ADN/R Class:	2 5F
Class	2.1
Class Label	2.1 2.1
Label 14.4 Packing group	2.1
Label	
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards:	Void
Label 14.4 Packing group ADR, IMDG, IATA	2.1
14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user	Void
14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler):	Void  No Warning: Gases.
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler): EMS Number:	Void  No Warning: Gases
14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler):	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat.
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler): EMS Number:	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler): EMS Number:	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity about the capacity and litres.
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler): EMS Number:	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category
14.4 Packing group ADR, IMDG, IATA  14.5 Environmental hazards: Marine pollutant:  14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Label 14.4 Packing group ADR, IMDG, IATA 14.5 Environmental hazards: Marine pollutant: 14.6 Special precautions for user Danger code (Kemler): EMS Number:	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity at 1 litre: Category B. For WASTE AEROSOLS: Category, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of
14.4 Packing group ADR, IMDG, IATA  14.5 Environmental hazards: Marine pollutant:  14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Code	Void  No  Warning: Gases.  F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity about 1 litre: Category B. For WASTE AEROSOLS: Category



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

	(Contd. of page
	subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann	nex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
• • •	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

Class	Share in %
NK	75-<100

- · VOC-CH 98.20 %
- · VOC-EU 649.1 g/l
- · Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

- · Department issuing SDS: Research & Development
- · Contact: info@petromark.eu
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 9)



Printing date: 24.10.2016 Version: 4 Revision: 18.10.2016

Trade name: 20313 PM Xeramic® Chain & Engine Cleaner

(Contd. of page 8)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

\_ CI