

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 20434 Xeramic Moto Fuel Stabiliser & Conditioner
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture -**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - Petromark Automotive Chemicals B.V.
 - Rooswijkweg 316
 - NL-1951 ME Velsen-Noord
 - The Netherlands
 - www.petromark.eu
 - info@petromark.eu
 -
- **Further information obtainable from:** Research & Development: info@petromark.eu
- **1.4 Emergency telephone number:** During normal business hours: Tel: +31 251 211397

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 - The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
 - Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%
- **Hazard statements**
 - H304 May be fatal if swallowed and enters airways.
- **Precautionary statements**
 - P101 If medical advice is needed, have product container or label at hand.
 - P102 Keep out of reach of children.
 - P103 Read label before use.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P280 Wear protective gloves / eye protection / face protection.
 - P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 - P331 Do NOT induce vomiting.
 - P403 Store in a well-ventilated place.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
 - EUH066 Repeated exposure may cause skin dryness or cracking.
 - EUH208 Contains α, α' -propylenedinitrilodi-o-cresol. May produce an allergic reaction.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

Trade name: 20434 Xeramic Moto Fuel Stabiliser & Conditioner

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons,C10-C13,n-alkanes,cyclic,<2%aromates, Benzene <0.1% Asp. Tox. 1, H304	75-<100%
CAS: 94-91-7 EINECS: 202-374-2	α,α' -propylenedinitrilodi-o-cresol Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥ 0.1 -<0.25%

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

Trade name: 20434 Xeramic Moto Fuel Stabiliser & Conditioner

(Contd. of page 2)

- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
- Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**
- Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

OEL Short-term value: 1200 mg/m³, 184 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

- **Protection of hands:**



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

Trade name: 20434 Xeramic Moto Fuel Stabiliser & Conditioner

(Contd. of page 3)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm
· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:
Form: Fluid

Colour: Clear

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition
Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 184-214 °C

· Flash point: 65 °C

· Flammability (solid, gas): Not applicable.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Explosion limits:
Lower: 0.6 Vol %

Upper: 6 Vol %

· Vapour pressure at 20 °C: 0.5 hPa

· Density at 20 °C: 0.79 g/cm³
· Bulk density: 790 kg/m³
· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water at 20 °C:

0.04 g/l

· Partition coefficient: n-octanol/water: >0.60206

(Contd. on page 5)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

Trade name: 20434 Xeramic Moto Fuel Stabiliser & Conditioner

(Contd. of page 4)

· Viscosity:	
Dynamic:	Not determined
Kinematic at 40 °C:	1.3 mm ² /s
· Solvent content:	
Organic solvents:	99.0 %
· Solids content:	
	0.0 %

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	4951 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene <0.1%

EL0 (48h)	1000 mg/l (Daphnia magna)
EL0(72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0(96h)	1000 mg/l (Oncorhynchus mykiss (96h))

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

Trade name: 20434 Xeramic Moto Fuel Stabiliser & Conditioner

(Contd. of page 5)

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
- HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|-----------------|
| · 14.1 UN-Number | Void |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.2 UN proper shipping name | Void |
| · ADR, ADN, IMDG, IATA | Void |
| · 14.3 Transport hazard class(es) | |
| · ADR, IMDG, IATA | |
| · Class | Void |
| · ADN | Void |
| · ADN/R Class: | - |
| · 14.4 Packing group | Void |
| · ADR, IMDG, IATA | Void |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user | Not applicable. |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

(Contd. on page 7)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date: 14.02.2020

Version: 1

Revision: 14.02.2020

Trade name: 20434 Xeramic Moto Fuel Stabiliser & Conditioner

(Contd. of page 6)

· **National regulations:**

Class	Share in %
NK	75-<100

- **VOC-CH** 98.96 %
- **VOC-EU** 781.8 g/l
- **Danish MAL Code** 1-1
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

· **Contact:** info@petromark.eu

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity - oral – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered. ***